

## Shell Kit for Pumpfix F, without nozzles, bl.cover

### Article information

Item no.: 24000S-RBK  
GTIN: 4026092097069  
Price group: 30

### Description

KESSEL shell kit for Pumpfix F, without sockets, black cover

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating a Pumpfix F backwater pumping station.

#### General characteristics

|                          |                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Colour:                  | black                                                                                                                      |
| Type of wastewater:      | with sewage                                                                                                                |
| Installation situation:  | floor slab installation                                                                                                    |
| Delivery state:          | Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected) |
| Inlet max. scoring (DN): | Z-53.2-388                                                                                                                 |
| Motor type:              | KSM 140                                                                                                                    |
| Protection class (pump): | IP 68 (3m/48h)                                                                                                             |

#### Dimensions

|                                                        |                                     |
|--------------------------------------------------------|-------------------------------------|
| Net weight:                                            | 15,2 kg                             |
| Gross weight:                                          | 18 kg                               |
| Groundwater resistant from lower edge of base section: | 3000 mm                             |
| Cutout dimension, width:                               | 750 mm                              |
| Cutout dimension, length:                              | 750 mm                              |
| Vertical drop between inlet and outlet:                | 9 mm                                |
| Installation depth:                                    | 516 - 669 mm                        |
| Vertical adjustment:                                   | vertically adjustable upper section |
| Packaging dimension:                                   | length                              |
| Packaging dimension:                                   | width                               |
| Packaging dimension:                                   | height                              |

#### Tank/drain body

|         |          |
|---------|----------|
| System: | optional |
|---------|----------|

#### Coverage features

|                |                                |
|----------------|--------------------------------|
| Type of cover: | Cover plate with slotted cover |
|----------------|--------------------------------|

|                    |                  |
|--------------------|------------------|
| Cover material:    | Polymer          |
| Colour of cover:   | black            |
| Width of cover:    | 366 mm           |
| Length of cover:   | 366 mm           |
| Drainage function: | yes              |
| Cover locking:     | Lock & Lift      |
| Load class:        | L 15 (EN 1253-1) |
| Odour trap:        | Multistop        |