

Practicus drain body DN 50, Vertical outlet



Article information

Item no.: 45250
GTIN: 4026092033579
Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

System:	125
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Inlet max. scoring (DN):	Z-19.53-2414,Z-19.17-1719

Dimensions

Net weight:	0,59 kg
Gross weight:	0,7 kg
Diameter:	135 mm
Height:	191 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Number of outlets:	1
Material of drain body:	PP

System: vertical

Coverage features

Odour trap: included