

Chamber module LW 1000 floor slab Access LW 600, 880-1129 mm, Class D



Article information

Item no.: 8740013
GTIN: 4026092065280
Price group: 60

Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

Description

Variant

Note on installation depth:

A load distribution slab must be installed on site for load class D

General characteristics

Colour:

black

Material:

PE-HD

Standard:

EN 13598-2

Installation situation:

underground installation

Delivery state:

Partly for on-site assembly (access steps have been pre-mounted in the factory)

Inlet max. scoring (DN):

Z-42.1-527

Dimensions

Net weight:

108,5 kg

Gross weight:

125 kg

Groundwater resistant from lower edge of base section:

3000 mm

Installation depth:

880 - 1129 mm

Vertical adjustment:

vertically adjustable upper section

Length:

1200 mm

Width:

1200 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Number of inlets:	150 mm
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	600 mm
Coverage features	
Type of cover:	Round cover plate
Cover material:	Grey iron
Colour of cover:	black
Width of cover:	659 mm
Height of cover:	122 mm
Length of cover:	659 mm
Surface:	Grey iron
Cover locking:	locked
Load class:	D 400 (EN 124)
Tightness:	surface water resistant